

20-30-45FT BULK CONTAINERS



BULK UNIT - 20/30FT

In addition to the 45ft bulk container, UNIT45 is offering 20ft and 30ft palletwide bulk containers suited for road and rail transport. All bulk container designs can also accommodate general cargo including palletised goods, thus reducing the need for empty backhauls. All bulk designs are

fitted with a 'letterbox' discharge hatch, enabling them to be discharged using tipping trailers. Conventional double doors are fitted to the other end of all the bulk containers in our fleet. Stainless steel hatches are provided for top loading.

45FT BULK CONTAINER

external dimensions	internal dimensions	door opening	discharge hatch
length: 13716 mm	length: 13506 mm	door width: 2416 mm	hatch width: 1748 mm
width: 2500 mm	width: 2438 mm	door height: 2585 mm	hatch height: 400 mm
height: 2896 mm	height: 2679 mm		
ratings	capacity		
max. gross weight: 45200 kgs	88.2 m ³		
tare weight: 5200 kgs	7 loading hatches ø 500 mm		
max. payload: 40000 kgs			

30FT BULK CONTAINER

external dimensions	internal dimensions	door opening	bulk door opening
length: 9125 mm	length: 8913 mm	door width: 2416 mm	bulk door width: 1072 mm
width: 2500 mm	width: 2438 mm	door height: 2432 mm	bulk door height: 1832 mm
height: 2743 mm	height: 2526 mm		
discharge hatch	ratings	capacity	
hatch width: 2144 mm	max. gross weight: 30480 kgs	54.8 m ³	
hatch height: 400 mm	tare weight: 3360 kgs	4 loading hatches ø 500 mm	
	max. payload: 27120 kgs		

20FT BULK CONTAINER

external dimensions	internal dimensions	door opening	bulk door opening
length: 6058 mm	length: 5898 mm	door width: 2416 mm	bulk door width: 1072 mm
width: 2500 mm	width: 2438 mm	door height: 2432 mm	bulk door height: 1832 mm
height: 2743 mm	height: 2518 mm		
discharge hatch	ratings	capacity	
hatch width: 2144 mm	max. gross weight: 32000 kgs	36.3 m ³	
hatch height: 400 mm	tare weight: 2470 kgs	3 or 4 loading hatches ø 500 mm	
	max. payload: 29530 kgs		



- STAINLESS STEEL ROOF & DISCHARGE HATCHES



MORE INFO