

53FT DRY SAFETY CONTAINERS



In addition to our standard 53ft dry container, UNIT53 Inc. has developed the 53ft intermodal safety container, the most secure and reliable solution for transporting cargo across road, rail, or water. Equipped with reinforced doors, safety pins, and plates, this container provides superior protection against theft and tampering.

For added security, options include the Power In-Lock system and lock box. To support efficient logistics, the container can be fitted

with Traxens tracking on the door (or any provider of choice), allowing you to monitor cargo from loading to unloading. This ensures full visibility and peace of mind.

Built with sustainability in mind, the unit features a bamboo floor and waterborne paint, reducing environmental impact while delivering strength and durability. Choose our safety container for a solution that combines safety, security, and sustainability, giving you confidence in every shipment.

external dimensions

length: 53ft / 16154 mm
width: 8ft 6^{3/8} inch / 2600 mm
height: 9ft 6^{1/4} inch / 2902 mm

internal dimensions

length: 52ft 6^{47/64} inch / 16021 mm
width: 8ft 3^{3/32} inch / 2517 mm (between posts)
width: 8ft 3^{7/16} inch / 2526 mm (between side panel)
height: 9ft 1^{3/32} inch / 2771 mm

door opening

door width: 8ft 2^{31/32} inch / 2514 mm
door height: 9ft 1^{1/4} inch / 2775 mm

ratings

max. gross weight: 67200 lbs / 30480 kgs
tare weight: 10580 lbs / 4800 kgs
max. payload: 56620 lbs / 25680 kgs

capacity

3960 cubic feet / 112,1 m³



- OPTIONAL TRACK & TRACE SYSTEM WITH DOOR SENSOR AND GEO-FENCE
- STANDARD DOORPINS AND EXTRA STRONG DOORS
- OPTIONAL DOOR LOCK AND/ OR LOCKBOX ON THE DOOR
- 24/7 VISIBILITY AND CONTROL ON THE C SENCE CONTROL TOWER - www.csence.com
- STANDARD LASHING RINGS
- ENVIRONMENTALLY FRIENDLY BAMBOO FLOOR AND WATERBORNE PAINT

