

UNIT53

INTERMODAL INNOVATORS



53FT DRY CONTAINERS

UNIT53 Inc. (a subsidiary of UNIT45 B.V.) offers 53ft dry and refrigerated containers and is more than just an intermediary. It takes full responsibility for the financial arrangements with the factory and contracts separately with the end user regarding price, currency denomination and required delivery location.

UNIT53 Inc. engineers supervise the manufacturing process at the factory and liaise with classification surveyors to ensure that containers meet U.S. regulatory requirements. The company also arranges delivery from the factory to the locations nominated by the customer.

All of our 53ft containers are made from durable materials to ensure that the goods inside are protected during transportation. The containers allow for efficient and secure transportation of a wide range of products, from consumer goods to industrial materials. They are widely used in various industries, including retail, manufacturing, and logistics.

Our 53ft dry container offers a high cubic capacity and payload. By using special high-strength steels and lightweight floor materials, an extremely low tare weight has been achieved. Equipped with a bamboo floor and coated with

waterborne paint our containers ensure sustainability and reduce your carbon footprint. For domestic transportation our 53ft containers offer the most space to accommodate a large volume of cargo.

For customers wanting to add our 53ft containers to their fleet, UNIT53 Inc. offers a range of financial solutions to suit most requirements.

Have a look at our website www.unit53.com for more information.



MORE INFO

UNIT53 DRY SPECIFICATIONS

DRY UNIT

external dimensions

length: 53ft / 16154 mm

width: 8ft 6³/₈ inch / 2600 mm

height: 9ft 6¹/₄ inch / 2902 mm

internal dimensions

length: 52ft 6⁴⁷/₆₄ inch / 16021 mm

width: 8ft 3³/₃₂ inch / 2517 mm (between posts)

width: 8ft 3⁷/₁₆ inch / 2526 mm (between side panel)

height: 9ft 1³/₃₂ inch / 2771 mm

door opening

door width: 8ft 2³¹/₃₂ inch / 2514 mm

door height: 9ft 1¹/₄ inch / 2775 mm

ratings

max. gross weight: 67200 lbs / 30480 kgs

tare weight: 10360 lbs / 4700 kgs

max. payload: 56840 lbs / 25780 kgs

capacity 3960 cubic feet / 112,1 m³



- STANDARD LASHING RINGS
- ENVIRONMENTALLY FRIENDLY BAMBOO FLOOR AND WATERBORNE PAINT

