

UNIT45's palletwide dry freight container offers the highest cubic capacity and payload of any standard 45ft container design. By using special high-strength steels and lightweight floor materials, an extremely low tare weight has been achieved.

In-service experience in the testing environment of European shortsea shipping where round-trip cycles are short and handling frequent, has been excellent, proving the strength and durability of the UNIT45 design. With their chamfered corner posts and euro corner castings, all UNIT45 containers are road-legal throughout the EU and are

also well suited for transport on cellular and non-cellular container ships, ro-ro vessels, inland waterway barges and rail wagons.

The precise specification of our 45ft palletwide container can be modified to meet differing needs. The height and width can be varied to meet customers' need or restrictions on certain routes. And while our standard stacking height capabilities exceed most shortsea users' requirements, these can be uprated if necessary. These 10'6ft high dry containers have especially been built higher for, for instance, the white good industry (kitchen appliances) and the paper industry. These industries are in need of containers with a higher internal height to transport higher stacked pallets or paper rolls that do not fit in a container with regular height.

UNIT45 can modify and build containers with an external height varied from 9'6ft up to 10'6ft high and all in between, to meet customers' needs.






WARRANTY the paint system applied on the container surface is guaranteed against corrosion and/or paint failure for a period of five years.

All containers are guaranteed against any defects or omissions in construction, poor workmanship or defective materials for a period of two years.

All decals will be guaranteed for a period of seven years against colour fade, adhesive and peeling.



DRY FREIGHT CONTAINER 10'6 TYPE A+: LIGHTWEIGHT BAMBOO FLOOR

external dimensions internal dimensions door opening length: 13716 mm length: 13556 mm door width: 2500 mm width: 2438 mm door height: height: 3200 mm

height: 2998 mm 2416 mm 2960 mm

capacity

europallet (1200mm x 800mm) 33 99,1m³ iso pallet (1200mm x 1000mm) 26

ratings

max. gross weight: 34000 kgs tare weight: 4640 kgs max. payload: 29360 kgs

DRY FREIGHT CONTAINER 10'6 TYPE A: BIRCH FLOOR

external dimensions internal dimensions door opening

length: 13716 mm length: 13556 mm door width: 2416 mm 2960 mm width: 2500 mm width: 2438 mm door height: 3200 mm 2998 mm height: height:

capacity

99,1m³ europallet (1200mm x 800mm) 33 iso pallet (1200mm x 1000mm) 26

ratinas

max. gross weight: 34000 kgs tare weight: 4580 kgs max. payload: 29420 kgs

- ENVIRONMENTALLY FRIENDLY BAMBOO FLOOR
- SPECIAL INTERMEDIATES AND HIGH DOORS
- WATERBORNE PAINT

