

UNIT53 Inc. (a subsidiary of UNIT45 B.V.) offers 53ft dry and refrigerated containers and is more than just an intermediary. It takes full responsibility for the financial arrangements with the factory and

contracts separately with the end user regarding price, currency denomination and required delivery location.

In addition to our standard 53ft dry container, UNIT53 Inc. has recently developed the 53ft intermodal safety container, the most secure and reliable solution for transporting your cargo. Whether it's through road, rail, or water, you can trust our safety container to ensure the safe transport of your goods. With Traxens (optional) tracking on the door, you can easily trace the whereabouts of your cargo at any given

time, from the loading to the unloading location. All other tracking providers are certainly possible. This feature provides peace of mind and allows for efficient logistics management. Our safety container is designed with solid doors, reinforced with safety pins and plates, providing an extra layer of protection against theft and tampering. We also offer the optional Power In-Lock lock and/or lock box for enhanced security.

Equipped with lashing rings, our safety container allows for secure and stable stacking of cargo, minimizing the risk of damage during transit. Not only is our safety container built for security, but it is also environmentally conscious. It features a bamboo floor, ensuring sustainability and reducing your carbon footprint.

Additionally, the container is coated with waterborne paint, further promoting eco-friendliness. Choose our innovative safety container for the utmost peace of mind and reliable transportation of your cargo. Trust in our commitment to safety, security and sustainability.

For customers wanting to add our 53ft containers to their fleet, UNIT53 Inc. offers a range of financial solutions to suit most requirements.

Have a look at our website www.unit53.com for more information.



MORE INFO



DRY UNIT

external dimensions

internal dimensions

length: 53ft / 16154 mm

length: 52ft 647/64 inch / 16021 mm

8ft 6^{3/8} inch / 2600 mm width: height: 9ft 61/4 inch / 2902 mm

8ft 3^{3/32} inch / 2517 mm (between posts) width: width: 8ft 3^{7/16} inch / 2526 mm (between side panel)

height: 9ft 13/32 inch / 2771 mm

door opening

door width: 8ft 2^{31/32} inch / 2514 mm 9ft 11/4 inch / 2775 mm door height:

ratings

max. gross weight: 67200 lbs / 30480 kgs 10580 lbs / 4800 kgs tare weight: 56620 lbs / 25680 kgs max. payload:

3960 cubic feet / 112.1 m³ capacity



- OPTIONAL TRACK & TRACE SYSTEM WITH DOOR SENSOR AND GEO-FENCE
- STANDARD DOORPINS AND **EXTRA STRONG DOORS**
- OPTIONAL DOOR LOCK AND/ OR LOCKBOX ON THE DOOR
- 24/7 VISIBILITY AND CONTROL ON THE C SENCE CONTROL TOWER www.csence.com
- STANDARD LASHING RINGS
- ENVIRONMENTALLY FRIENDLY BAMBOO FLOOR AND WATERBORNE PAINT















