

UNIT53 SPECIFICATIONS

DRY UNIT

external dimensions

length: 16154 mm / 53ft

width: 2600 mm / 8ft 6^{23/64} inch

height: 2908 mm / 9ft 6^{1/2} inch

internal dimensions

length: 16000 mm / 52ft 5^{29/32} inch

width: 2550 mm / 8ft 4^{5/8} inch (between s.b.r.)

width: 2557 mm / 8ft 4^{21/32} inch (between side panel)

height: 2780 mm / 9ft 1^{7/16} inch

door opening

door width: 2492 mm / 8ft 2^{7/64} inch

door height: 2781 mm / 9ft 1^{1/2} inch

ratings

max. gross weight: 30480 kgs / 67200 lbs

tare weight: 4640 kgs / 10230 lbs

max. payload: 25840 kgs / 56970 lbs

capacity 114 m³ / 4025 cubic feet



DIESEL-ELECTRIC REEFER

external dimensions

length: 16154 mm / 53ft

width: 2600 mm / 8ft 6^{23/64} inch

height: 2908 mm / 9ft 6^{1/2} inch

internal dimensions

length: 15345.5 mm / 50ft 4^{31/64} inch

width: 2470 mm / 8ft 1^{15/64} inch

height: 2566 mm / 8ft 5 inch

door opening

door width: 2470 mm / 8ft 1^{15/64} inch

door height: 2568 mm / 8ft 8^{41/64} inch

ratings

max. gross weight: 30480 kgs / 67200 lbs

tare weight: 5940 kgs / 13100 lbs

max. payload: 24540 kgs / 54100 lbs

capacity 96.3 m³ / 3400 cubic feet

capacity fuel tank 450 l / 118.8 gallons



- OPTIONAL TRACK & TRACE
- OPTIONAL DOUBLE STACK
- OPTIONAL A-TRACK

UNIT53.com