

# UNIT53 DRY SPECIFICATIONS

## DRY UNIT

### external dimensions

length: 16154 mm / 53ft

width: 2600 mm / 8ft 6<sup>3/8</sup> inch

height: 2902 mm / 9ft 6<sup>1/4</sup> inch

### internal dimensions

length: 16021 mm / 52ft 6<sup>47/64</sup> inch

width: 2517 mm / 8ft 3<sup>3/32</sup> inch (between posts)

width: 2526 mm / 8ft 3<sup>7/16</sup> inch (between side panel)

height: 2771 mm / 9ft 1<sup>3/32</sup> inch

### door opening

door width: 2514 mm / 8ft 2<sup>31/32</sup> inch

door height: 2775 mm / 9ft 1<sup>1/4</sup> inch

### ratings

max. gross weight: 30480 kgs / 67200 lbs

tare weight: 4700 kgs / 10360 lbs

max. payload: 25780 kgs / 56840 lbs

capacity 112.1 m<sup>3</sup> / 3960 cubic feet



- STANDARD LASHING RINGS
- ENVIRONMENTALLY FRIENDLY BAMBOO FLOOR AND WATERBORNE PAINT
- OPTIONAL TRACK & TRACE

# UNIT53 REEFER SPECIFICATIONS

## DIESEL REEFER

### external dimensions

length: 16154 mm / 53ft  
width: 2600 mm / 8ft 6<sup>23/64</sup> inch  
height: 2908 mm / 9ft 6<sup>1/2</sup> inch

### internal dimensions

length: 15345.5 mm / 50ft 4<sup>31/64</sup> inch  
width: 2470 mm / 8ft 1<sup>15/64</sup> inch  
height: 2566 mm / 8ft 5 inch

### door opening

door width: 2470 mm / 8ft 1<sup>15/64</sup> inch  
door height: 2568 mm / 8ft 8<sup>41/64</sup> inch

### ratings

max. gross weight: 30480 kgs / 67200 lbs  
tare weight: 6170 kgs / 13600 lbs  
max. payload: 24310 kgs / 53600 lbs

capacity 97.3 m<sup>3</sup> / 3436 cubic feet

capacity fuel tank 450 l / 118.8 gallons



- OPTIONAL TRACK & TRACE
- OPTIONAL DOUBLE STACK
- OPTIONAL A-TRACK