

UNIT53

INTERMODAL INNOVATORS



53FT DRY CONTAINERS

UNIT45 B.V. was established in Rotterdam in 2002 specifically to develop and market 45ft pallet-wide containers. Through years of experience and putting its clients need first UNIT45 B.V. has grown to be a true intermodal innovator, by not only focusing on 45ft containers but also beyond adding the 20ft, 30ft, 40ft, 48ft, 51ft and 53ft to its portfolio.

A standard range of containers, including dry units, all-electric, diesel-electric reefers and curtain-sided units, has been developed and these can be tailored to meet individual

operators' requirements. UNIT53 Inc. (a subsidiary of UNIT45 B.V.) designs are constantly revised to take account of new technology and materials as they become available and proven in service.

However, UNIT53 Inc. is more than just an intermediary. It takes full responsibility for the financial arrangements with the factory and contracts separately with the end user regarding price, currency denomination and required delivery location. UNIT53 Inc. engineers supervise the manufacturing

process at the factory and liaise with classification surveyors to ensure that containers meet international regulatory requirements. The company also arranges delivery from the factory to the locations nominated by the customer.

For customers wanting to add the 53ft containers to their fleet, UNIT53 Inc. offers a range of financial solutions to suit most requirements.

Have a look at our brand new website www.unit53.com for more information.

UNIT53 DRY SPECIFICATIONS

DRY UNIT

external dimensions

length: 16154 mm / 53ft

width: 2600 mm / 8ft 6^{3/8} inch

height: 2902 mm / 9ft 6^{1/4} inch

internal dimensions

length: 16021 mm / 52ft 6^{47/64} inch

width: 2517 mm / 8ft 3^{3/32} inch (between posts)

width: 2526 mm / 8ft 3^{7/16} inch (between side panel)

height: 2771 mm / 9ft 1^{3/32} inch

door opening

door width: 2514 mm / 8ft 2^{31/32} inch

door height: 2775 mm / 9ft 1^{1/4} inch

ratings

max. gross weight: 30480 kgs / 67200 lbs

tare weight: 4700 kgs / 10360 lbs

max. payload: 25780 kgs / 56840 lbs

capacity 112.1 m³ / 3960 cubic feet



- STANDARD LASHING RINGS
- ENVIRONMENTALLY FRIENDLY BAMBOO FLOOR AND WATERBORNE PAINT
- OPTIONAL TRACK & TRACE